

PRODUCT DATA SHEET

DLK 10

LAUDA through-flow coolers upgrade any type of heating thermostat with pump connections to a high-quality cooling thermostat and thus allow working below ambient temperature. Through-flow coolers replace cooling with tap water that is expensive and ecologically not recommendable. They provide a constant flow and temperature of cooling supply regardless of the variations. Therefore, it is possible to ensure optimum temperature stability over the entire period and allow reproducible temperature conditions at any time.



Working temperature min.
-15 °C



Working temperature max.
150 °C

Technical Attributes	DLK 10
Working temperature min.	-15 °C
Working temperature max.	150 °C
Cooling output at 20°C measured with ethanol	0.22 kW
Cooling output at 0°C measured with ethanol	0.12 kW
Cooling output at -10°C measured with ethanol	0.08 kW
Power consumption	0.2 kW
Dimensions (WxDxH) in mm	200x400x320

LAUDA DR. R. WOBSEY GMBH & CO. KG
Pfarrstraße 41/43 · 97922 Lauda-Königshofen
Postfach 1251 · 97912 Lauda-Königshofen · DE

T +49 (0) 9343 503-0 · F +49 (0) 9343 503-222
info@lauda.de · www.lauda.de
WEEE-Reg.-Nr.: DE 66 42 40 57

Kommanditgesellschaft: Sitz Lauda-Königshofen
Registergericht Mannheim · HRA 560069

Persönlich haftende Gesellschafterin:
LAUDA DR. R. WOBSEY Verwaltungs-GmbH
Sitz Lauda-Königshofen
Registergericht Mannheim · HRB 560226

Geschäftsführer:
Dr. Gunther Wobser (Vors.), Dr. Mario Englert
Dr. Marc Stricker
Beirat: Dr. Gerhard Wobser