# **NEW!** Thermo Scientific™ Forma™ 89000 Series Ultra-Low Freezers

Dependable -80°C storage with energy-savings and sustainability features

- Low peak variation helps ensure sample protection throughout entire cabinet
- Fast door opening recovery in as little as 13 minutes
- **0.93°C steady-state temperature** variation over time
- Long warm-up time from -80°C to -50°C in 5 hours
- Four capacities: 300, 400, 500 and 600 2-inch (5cm) box
- Water-cooled condenser option: reduces heat output by almost 60%\*\*\*

#### Designed to keep your and lower HVAC costs samples safe


- Worry-free storage. With low peak variation, samples are protected throughout the entire cabinet.1
- Records temperature and events

# Limit environmental impact

- Uses as low as 9.4 kWh/day, depending on size
- Less heat emission lowers HVAC costs
- Natural refrigerants compliant with EU F-Gas regulation: R170 and R290
- Environmentally-friendly, water-blown foam insulation
- Manufactured in an award-winning, zero-waste to landfill facility

#### **User-friendly and quiet**

- Completely new freezer and user interface.
- Quiet enough to reside directly in the laboratory. At just 50 dBA, the sound is comparable to a home refrigerator.<sup>2</sup>



- 2. All data based on internal data unless otherwise noted. Data on file.
- 3. \* ENERGY STAR certified on select models
- 4 \*\*\*Water-cooled condenser option available on 230V/50Hz, 400-600 box capacity models and 208-230V/60Hz, 600 box capacity only.



User friendly touch-screen interface and cabinet



- Capacitive touch even when using latex gloves
- Touch-screen datalogging and temperature mapping eliminates the need for a separate chart recorder
- Built-in USB port for exporting data
- Advanced security features: alarm settings, password-protected controller, padlock-compatible doors and optional access card entry
- Ergonomic design: comfortable door handle, eye-level touch-screen and shelf-level placement that do not require floor-level loading of racks
- Four inner doors minimize ambient temperature during sample retrieval



#### **Specifications & Ordering Information**

Upright	Upright Freezers (-50°C to -86°C)										
	Сар	acity			Max. Shelf			Shipping			
Model Number	liters	5cm (2") cryobox	Electrical	Amps / Breaker (Plug)	Weight kg	Interior Dimensions H x W x D cm	Exterior Dimensions H x W* x D cm	Weight kg			
8930086V	422	300	230V / 50Hz	5.9/10 (European)	57	130.1 x 45.2 x 71.9	198.1 x 58.4 x 96	323			
8930086D	422	300	208-230V / 60Hz	5.6/15 (NEMA 6-15)	57	130.1 X 45.2 X 7 1.9	190.1 X 50.4 X 90				
8940086V	549	400	230V / 50Hz	5.3/10 (European)	7.5	1001500710	198.1 x 71.9 x 96	010			
8940086D	549	400	208-230V / 60Hz	5.9/15 (NEMA 6-15)	75	130.1 x 58.8 x 71.9		312			
8950086V	600	500	230V / 50Hz	5.9/10 (European)	- 93	120 1 2 72 0 2 71 0	100 1 4 96 4 4 06**	200			
8950086D	682	500	208-230V / 60Hz	5.0/15 (NEMA 6-15)	93	130.1 x 73.0 x 71.9	198.1 x 86.4 x 96**	333			
8960086V	010	000	230V / 50Hz	6.1/10 (European)	444	100 1 07 0 71 0	100 1 100 0 00**	372			
8960086D	816	600	208-230V / 60Hz	6.2/15 (NEMA 6-15)	111	130.1 x 87.3 x 71.9	198.1 x 100.6 x 96**				

<sup>\*</sup> Allowance for handle and hinge, add 10.7 cm to cabinet width

<sup>\*\*</sup> Doorway width clearance is 87.6 cm for 8950086 and 8960086



Performance Data									
Model Number	Energy Consumption (kW-hr/day)* Standard Mode	Peak Variation from -80°C setpoint (°C)**	Door Opening Recovery (minutes)	Warm Up Time (-80°C to -50°C) (minutes)***	Noise Level (dBA)				
8930086	9.4	+8.5 / -2.4	13	254	52				
8940086	9.8	+8.7 / -1.2	15	262	52				
8950086	10.8	+6.6 / -1.0	21	258	50				
8960086	11.5	+6.5 / -0.8	26	300	50				

<sup>\*</sup> Energy Calculation: Typical freezer data based on internal testing with freezer setpoint at -80°C and ambient temperature at 20°C

<sup>\*\*\*</sup> Warm Up Time: Typical freezer data based on internal testing with freezer setpoint at -80°C and ambient temperature at 20°C



<sup>\*\*</sup>Peak Variation From Setpoint: Typical freezer data based on internal testing with freezer setpoint at -80°C and ambient temperature at 20°C

## Thermo Scientific™ Forma™ 89000 Series Ultra-Low Freezers

## Options and Accessories (Field Installed must be installed by a qualified professional)

Options	Installation	8930086	8940086	8950086	8960086
LN2 Backup System	Factory Installed	N/A	LN4567	LN4567	LN4567
Maintains temperature down to -80°C with liquid nitrogen. Models for 89300 are stand alone.	Field Installed	FLN300V* FLN300W**	FLN4567LE	FLN4567LE	FLN4567LE
CO2 Backup System	Factory Installed	N/A	CO4567	CO4567	CO4567
Maintains temperature down to -67°C with CO2. Models for 89300 are stand alone.	Field Installed	FCO300V* FCO300W**	FCO4567LE	FCO4567LE	FCO4567LE
Chart Recorder (Inkless)	Factory Installed	N/A	CR4567	CR4567	CR4567
6" (15.2 cm), seven day inkless recorder, -115° to +50°C, +5°C resolution	Field Installed	N/A	FCR400LE	FCR500LE	FCR600LE
Chart Recorder (Ink)	Factory Installed	N/A	CRP4567	CRP4567	CRP4567
6" (15.2 cm), seven day inkless recorder, $$ -115° to +50°C, +5°C resolution	Field Installed	6383-6V* 6383-6W**	FCRP400LE	FCRP500LE	FCRP600LE
Access Key Option Card	Factory Installed	RAC34567	RAC34567	RAC34567	RAC34567
Access control. Includes five key cards. Supports ISO15693 and ISO14443 protocols.	Field Installed	FAC34567LE	FAC34567LE	FAC34567LE	FAC34567LE
Stainless Steel Freezer Interior	Factory Installed	SS34567	SS34567	SS34567	SS34567
Twist Lock Plug	Factory Installed	US230V15ATL	US230V15ATL	US230V15ATL	US230V15ATL
NEMA L6-15P for 208-230V / 60Hz	Field Installed	TL230V15A	TL230V15A	TL230V15A	TL230V15A
Twist Lock Plug	Factory Installed	US230V20ATL	US230V20ATL	US230V20ATL	US230V20ATL
NEMA L6-20P for 208-230V / 60Hz	Field Installed	TL230V20A	TL230V20A	TL230V20A	TL230V20A
Water-Cooled Condenser Option***	Factory Installed	N/A	WC34567	WC34567	WC34567

Accessories	8930086	8940086	8950086	8960086
Access Key Pack: Includes five key cards.	ACE34567	ACE34567	ACE34567	ACE34567
Shelf Kit: Includes one shelf and shelf support clips	SK300	SK400	SK500	SK600
Chart Paper Ink (Pack of 50)	17020	17020	17020	17020
Chart Paper Inkless (Pack of 50)	N/A	6185	6185	6185
Replacement Air Filter	AF34567LE	AF34567LE	AF34567LE	AF34567LE
Replacement Back-Up Battery	400159	400159	400159	400159
Alarm Delay Module: Eliminates nuisance alarms due to intermittent or transitory conditions. Adjustable delaly requires alarm condition to exist for user defined period before signal is released to monitoring system.	6903	6903	6903	6903
Cryo Gloves Medium	4425	4425	4425	4425
Cryo Gloves Large	4426	4426	4426	4426
Seismic Restraint Kit	TF-ULT300	TF-ULT400	TF-ULT500	TF-ULT600

<sup>\*</sup>V = 230V/50Hz (European plug)



#### Find out more at thermofisher.com/cold

<sup>\*\*</sup>W = 230V/50Hz (UK plug)

<sup>\*\*\*</sup>Water-cooled condenser option available on 230V/50Hz, 400-600 box capacity models and 208-230V/60Hz, 600 box capacity only.

## Thermo Scientific<sup>™</sup> Forma<sup>™</sup> 89000 Series Ultra-Low Freezers

## **Racks for Boxes and Microplates**

Racks for 2" (5.08 cm) Boxes									
2" Box Racks	Model No.	Description	Dimensions H x W x D cm	Storage	89300	89400	89500	89600	
				Boxes Per Rack	25	25	25	25	
	920090	Sliding Drawer Rack	30.2 x 14 x 68.3	Racks Per Shelf	3	4	5	6	
To the same of				Racks Per Freezer	12	16	20	24	
				Boxes Per Freezer	300	400	500	600	
				Boxes Per Rack	25	25	25	25	
	1050500	Adjustable Side	29.5 x 13.7 x 67.9	Racks Per Shelf	3	4	5	6	
7777	1900020	1950520 Access Rack		Racks Per Freezer	12	16	20	24	
				Boxes Per Freezer	300	400	500	600	

Racks for 3" (7.62 cm) Boxes										
3" Box Racks	Model No.	Description	Dimensions H x W x D cm	Storage	89300	89400	89500	89600		
	000004		00.0 44 00.0	Boxes Per Rack	15	15	15	15		
1				Racks Per Shelf	3	4	5	6		
H	920091	Sliding Drawer Rack	30.2 x 14 x 68.3	Racks Per Freezer	12	16	20	24		
-				Boxes Per Freezer	180	240	300	360		

Racking Shelf Kits							
Description	Storage	89300	89400	89500	89600		
	Model No.	RSK300SD4	RSK400SD4	RSK500SD4	RSK600SD4		
Sliding Drawer Racks and 2" Boxes with 100 Count Cell Dividers (fits one shelf)	Racks Included	3	4	5	6		
(	Boxes Included	75	100	125	150		

Racks for Microplates									
Microplate Racks	Model No.	Description	Dimensions H x W x D cm	Storage	89300	89400	89500	89600	
	1950592	Side Access Rack with Locking Rod for Standard or Deepwell	30.2 x 14 x 65.3	Plates Per Rack	147	147	147	147	
				Racks Per Shelf	3	4	5	6	
	1930392			Racks Per Freezer	12	16	20	24	
				Plates Per Freezer	1764	2352	2940	3528	



## Thermo Scientific<sup>™</sup> Forma<sup>™</sup> 89000 Series Ultra-Low Freezers

#### **Boxes and Dividers**

Model No.	Description	# of Dividers	Quantity	Color
5026-0909	Thermo Scientific™ Nalgene™ polycarbonate 2" (5.08 cm) box for 1.2-2.0 mL vials	81	24	white
5954	2" (5.08 cm) fiberboard box	0	12	white
820002	2" (5.08 cm) fiberboard box	81	1	white
820109	2" (5.08 cm) fiberboard box	100	1	white
5956	3" (7.62 cm) fiberboard box	0	12	white
820003	3" (7.62 cm) fiberboard box	81	1	white
1950878	2" (5.08 cm) fiberboard box	0	12	multiple
1950879	2" (5.08 cm) fiberboard box	0	12	pink
1950880	2" (5.08 cm) fiberboard box	0	12	red
1950881	2" (5.08 cm) fiberboard box	0	12	yellow
1950882	2" (5.08 cm) fiberboard box	0	12	green
1950883	2" (5.08 cm) fiberboard box	0	12	blue
1950884	2" (5.08 cm) fiberboard box	0	12	black

#### **Fiberboard Dividers**

Model No.	Description	Quantity/Case
5958	Grid dividers for 100 12mm vials	12
6212	Grid dividers for 81 13mm vials	12
5960	Grid dividers for 64 14mm vials	12
5959	Grid dividers for 49 16mm vials	12

#### **Vials and Tubes**

Model No.	Description	Quantity/Case
377267	Thermo Scientific™ Nunc™ 1.8mL screw-top round-bottom vials with internal threading	1,800

Visit thermofisher.com for additional vials, tubes and sample storage consumables



## Thermo Scientific™ Forma™ 89000 Series Ultra-Low Freezers

## **Sliding Drawer Racks for Matrix and Cryobank Tubes**

		Freezer Model	89300	89400	89500	89600
200 μL Cap	acity Tubes					
		Rack Model No	1950787	1950787	1950787	1950787
	Thermo Scientific™ Matrix™ 200 µL 2D	Freezer Rack Dimensions W x H x D	14 x 30.3 x 68.5 cm			
3747, 3748,	Internally-threaded	Tubes per Box	96	96	96	96
4988	Universal Tubes	Boxes Per Rack	56	56	56	56
	Box Dimension: 8.5 x 12.8 x 2.75 cm	Racks Per Shelf	3	4	5	6
		Racks Per Freezer	12	16	20	24
		Tubes Per Freezer	64,512	86,016	107,520	129,024
500 μL Cap	acity Tubes					
	Thermo Scientific	Rack Model No	1950787	1950787	1950787	1950787
3734, 3735, 4898	Matrix 500 μL 2D Open Top Tubes Box Dimension: 8.5 x 12.8 x 2.6 cm	Freezer Rack Dimensions W x H x D	14 x 30.3 x 68.5 cm			
	Thermo Scientific™ Matrix™ 200 µL 2D with Duraseals Installed Internally-threaded Universal Tubes Box Dimension:	Tubes per Box	96	96	96	96
0700		Boxes Per Rack	56	56	56	56
3736, 3737,		Racks Per Shelf	3	4	5	6
4899		Racks Per Freezer	12	16	20	24
	8.5 x 12.8 x 2.75 cm	Tubes Per Freezer	64,512	86,016	107,520	129,024
		Rack Model No	1950791	1950791	1950791	1950791
374086, 374087 (including color options)	Thermo Scientific Nunc™ Cryobank™ 500 µl Internally Threaded Tubes Box Dimension: 8.5 x 12.8 x 3.5 cm	Freezer Rack Dimensions W x H x D	14 x 30.3 x 68.5 cm			
		Tubes per Box	96	96	96	96
3743, 3744,	Thermo Scientific Matrix 500 µL 2D	Boxes Per Rack	42	42	42	42
3745 (including	Internally Threaded ScrewTop Tubes	Racks Per Shelf	3	4	5	6
color options)	Box Dimension: 8.5 x 12.8 x 4.4 cm	Racks Per Freezer	12	16	20	24
(		Tubes Per Freezer	48,384	64,512	80,640	96,768



## Thermo Scientific™ Forma™ 89000 Series Ultra-Low Freezers

## **Sliding Drawer Racks for Matrix and Cryobank Tubes**

		Freezer Model	89300	89400	89500	89600
750 μL Cap	pacity Tubes					
3731, 3732, 4896	Thermo Scientific Matrix 750 µL 2D Open Top Tubes Box Dimension: 8.5 x 12.8 x 3.9 cm	Rack Model No	1950791	1950791	1950791	1950791
		Freezer Rack Dimensions W x H x D	14 x 30.3 x 68.5 cm			
3729, 4896	Thermo Scientific Matrix 750 µL 2D Tubes with Duraseals Installed Box Dimension: 8.5 x 12.8 x 3.9 cm	Tubes per Box	96	96	96	96
		Boxes Per Rack	42	42	42	42
		Racks Per Shelf	3	4	5	6
		Racks Per Freezer	12	16	20	24
		Tubes Per Freezer	48,384	64,512	80,640	96,768
1.0 mL Ca	pacity Tubes					
	Thermo Scientific Nunc Cryobank 1.0 mL Internally Threaded Tubes Box Dimension: 8.5 x 12.8 x 4.9 cm	Rack Model No	1950642	1950642	1950642	1950642
374088, 374089 (including color		Freezer Rack Dimensions W x H x D	14 x 30.3 x 68.5 cm			
		Tubes per Box	96	96	96	96
		Boxes Per Rack	35	35	35	35
options)		Racks Per Shelf	3	4	5	6
		Racks Per Freezer	12	16	20	24
		Tubes Per Freezer	40,320	53,760	67,200	80,640
3740, 3741, 3742 (including color options)	Thermo Scientific Matrix 1.0mL 2D Internally Threaded ScrewTop Tubes Box Dimension: 8.5 x 12.8 x 5.8 cm	Rack Model No	1950799	1950799	1950799	1950799
		Freezer Rack Dimensions W x H x D	14 x 30.3 x 68.5 cm			
		Tubes per Box	96	96	96	96
		Boxes Per Rack	28	28	28	28
		Racks Per Shelf	3	4	5	6
		Racks Per Freezer	12	16	20	24
		Tubes Per Freezer	32,256	43,008	53,760	64,512



## Thermo Scientific<sup>™</sup> Forma<sup>™</sup> 89000 Series Ultra-Low Freezers

#### **Sliding Drawer Racks for Matrix and Cryobank Tubes**

		Freezer Model	89300	89400	89500	89600
1.4 mL Cap	pacity Tubes					
3791, 3792, 4890	Thermo Scientific Matrix 1.4ml 2D Open Top Tubes Box Dimension: 8.5 x 12.8 x 4.9 cm	Rack Model No	1950642	1950642	1950642	1950642
		Freezer Rack Dimensions W x H x D	14 x 30.3 x 68.5 cm			
3801, 4890	Thermo Scientific Matrix 1.4mL 2D Tubes with Duraseals Installed Box Dimension: 8.5 x 12.8 x 4.9 cm	Tubes per Box	96	96	96	96
		Boxes Per Rack	35	35	35	35
3711, 3112, 4890	Thermo Scientific Matrix 1.4ml Human Readable Open Top Tubes Installed Box Dimension: 8.5 x 12.8 x 4.9 cm	Racks Per Shelf	3	4	5	6
		Racks Per Freezer	12	16	20	24
		Tubes Per Freezer	40,320	53,760	67,200	80,640
1.8 to 2.0 m	nL Capacity Tubes					
374500, 374501	Thermo Scientific Nunc 1.8 mL Externally-threaded Universal Tubes Box Dimension: 8.5 x 12.8 x 5.5 cm	Rack Model No	1950642	1950642	1950642	1950642
		Freezer Rack Dimensions W x H x D	14 x 30.3 x 68.5 cm			
	Thermo Scientific Nunc Cryobank 2.0 ml Internally Threaded Tubes Box Dimension: 8.5 x 12.8 x 5.5 cm	Tubes per Box	48	48	48	48
		Boxes Per Rack	35	35	35	35
374221, 374223		Racks Per Shelf	3	4	5	6
07.1220		Racks Per Freezer	12	16	20	24
		Tubes Per Freezer	20,160	26,880	33,600	40,320
5.0 mL Ca	pacity Tubes					
374220, 374222	Thermo Scientific Nunc Cryobank 5.0 ml Internally Threaded Tubes Box Dimension: 8.5 x 12.8 x 9.6 cm	Rack Model No	1950819	1950819	1950819	1950819
		Freezer Rack Dimensions W x H x D	14 x 30.3 x 68.5 cm			
		Tubes per Box	48	48	48	48
		Boxes Per Rack	21	21	21	21
		Racks Per Shelf	3	4	5	6
		Racks Per Freezer	12	16	20	24



