

## Labnet Mini Microcentrifuges

Simple and convenient to operate, the new Labnet mini microcentrifuges feature greater capacity (8-place microcentrifuge tubes and 4-place PCR strip rotors), a quick-release rotor system, and electronic brake.

Once samples are loaded and the lid is closed, the rotor rapidly accelerates to 6,000 rpm, making it an ideal centrifuge for bringing small droplets to the bottom of tubes for micro-filtrations or basic separations.

### Features

- ▶ Quick release rotor system – no tools needed to exchange rotors
- ▶ Electronic braking – Allows for more rapid deceleration, less waiting
- ▶ Dual lid switch
- ▶ Compact, rugged design
- ▶ 2-year warranty
- ▶ Compliance: CE/TUV/CSA



Ships standard  
with all six  
accessories



Available in 4  
different colors\*

\*Only the blue version is screened with  
the Labnet name and logo



## Product Specifications

Maximum Speed	6,000 rpm / 2,000 x g
Maximum Capacity	8 x 1.5/2.0mL or 4 x 0.2mL strips
Dimensions	6.8 x 5.8 x 4.8 in (17.2 x 14.7 x 12.2 cm)
Electrical	AC 100 - 240V, 50/60 Hz

## Ordering Information

Cat. No.	Description
C1601-B	Labnet mini centrifuge (blue lid)
C1601-P	Labnet mini centrifuge (purple lid)
C1601-R	Labnet mini centrifuge (red lid)
C1601-G	Labnet mini centrifuge (grey lid)

## Accessories

Cat. No.	Description	Qty/Pk
6770-RT	Rotor for 8 x 1.5/2.0 mL tubes	1
6770-RTS	Rotor for 4 x 8-strip tubes	1
6770-RTA.20	Individual adapters for 0.2 mL tubes, fits in rotor 6770-RT	8
6770-RTA.25	Individual adapters for 0.25 mL tubes, fits in rotor 6770-RT	8
6770-RTA.5	Individual adapters for 0.5 mL tubes, fits in rotor 6770-RT	8
401025	Power adapter, 24V	1



[www.labnetlink.com](http://www.labnetlink.com)

All rights reserved. Products described in this brochure are subject to availability and technical modification. Errors excepted. Corning Incorporated reserves the right to improve, enhance, or otherwise modify its products without prior notification. © 2020 Corning Incorporated. 9/20 CLSLN-EQ-011 REV1